



Product Overview

Altai BX500-X is an attractively priced 500 Mbps Point-to-Point outdoor radio unit with N-type connectors for external antenna connection, that operates in the 5 GHz band.

The BX500-X includes a field proven air interface that ensures best-in-class link connectivity in harsh spectrum for backhaul and access as well as wireless CCTV and additional applications that require robust connectivity. For this purpose, Altai BX500-X was designed to deliver an impressive packet switching power as well as jumbo frame support to guarantee full capacity, regardless of traffic packet size.

Enabling minimum TCO, Altai BX500-X is extremely reliable and durable, complying with IP67 standard. The unit features a built-in GPS for TDD synchronization. The unit also can be used as a subscriber unit for the BX600 series, enabling an initial low-cost deployment using PtP while seamlessly migrating to PtMP with network growth.

Product Highlights

- » Up to 500 Mbps PtP radio unit
- » 4.9 – 6.0 GHz
- » Up to 80 km
- » Built-in GPS
- » “Dying gasp” alert
- » Dynamic channel bandwidth
- » 350K packets-per-second
- » Supports Jumbo frames
- » Operates also as PtMP SU
- » Highly durable – IP67

Architecture

- Outdoor unit with connectors for external antenna (2 x N-type)

Network Interface

- Data Interface: 1 x 1 GE RJ45 Port with PoE PD
- PoE and ODU Interfaces: Outdoor CAT-5e; Maximum Cable Length: 75m for 1000Base-T

Radio

- Wireless Topology: PtP Unit / PtMP Subscriber Unit
- Maximum Capacity: 500 Mbps Net Aggregate Throughput (Up to 250 Mbps per Direction)
- Range: Up to 80 km
- Frequency: 4900 MHz – 6090 MHz *
- Channel Bandwidth: Configurable: 10, 20, 40, 80 MHz *
- Dynamic Bandwidth Selection: 20/40/80 MHz
- Modulation: OFDM (BPSK/QPSK/16QAM/64QAM/256 QAM)
- Error Correction: FEC k = 1/2, 2/3, 3/4, 5/6
- Adaptive Modulation/Coding: Supported
- Duplex Technology: TDD
- DFS: Supported *
- Automatic Channel Selection: Supported upon Power Up
- Antenna Modes: MIMO 2x2, Diversity, Adaptive MIMO/Diversity
- Dynamic Bandwidth Mgmt.: Committed Information Rate (CIR) and Best Effort Service Level (in PtMP Mode)
- Nomadic Mode: Supported (in PtMP Mode)
- Maximum TX Power: 26 dBm *
- Encryption: AES128
- TDD Synchronization: HSS Client Mode (Built-in GPS Receiver, HSS over Ethernet)
- Uplink/Downlink Allocation: Configurable: Symmetric or Asymmetric

Antenna

- External Antenna
- Antenna Connector: 2 x N-Female

Networking

- QoS: Packet Classification to 4 Priority Queues according to 802.1P or Diffserv
- VLAN Support: 802.1Q, QinQ, 4094 VLANs
- MTU Size: Up to 9216 bytes ***
- ODU Management: IPv4/IPv6 Dual-Stack; SNMPv1, SNMPv3; HTTP/HTTPS using Web Browser
- Dying Gasp Notification: Supported (for Remote PtP Unit)
- 802.1x: Supported (for PtMP Mode)
- Option 82: Supported (for PtMP Mode)
- DHCP Filtering: Supported (for PtMP Mode)
- IGMP Snooping: Supported (for PtMP Mode)
- PPPoE Filtering: Supported (for PtMP Mode)
- RADIUS Authorization: Supported (for PtMP Mode)
- RADIUS User Authentication: Supported
- Syslog: Supported

Physical Specification

- Dimension: 195 (w) x 125 (h) x 40 (d) mm
- Weight: 0.5 kg

Power Supply

- Power Consumption: < 13W
- Power Feeding: Power provided over ODU-IDU Cable
- PoE Input Voltage Range: 24 - 56VDC (PoE Voltage >= 55V is required for dying gasp support)

Environmental Specification

- Operating Temperature: -35 °C to 60 °C
- Humidity: 100% Condensing
- Enclosure Protection: IP67 per EN/IEC 60529, NEMA Type 4 Enclosure

Regulatory Compliance

Radio

- USA: FCC 47CFR Part 15.407
- EU: ETSI EN 301 893; ETSI 302 502

Safety

- USA: UL/CSA-C22.2 62368-1, UL/CSA-C22.2 60950-22
- EU: EN/IEC 62368-1, EN/IEC 60950-22

EMC

- USA: FCC 47CFR Part 15 Subpart B, Class B
- EU: ETSI EN 301 489-1, ETSI EN 301 489-4, ETSI 301 489-17

Product Ordering Information

BX500-X (Part No.: AT-2954-62C5)

- BX500-X PtP Unit
- Mounting Kit
- IP67 Cable Gland

Optional Accessories

- PoE Injector with DC Input 24VDC – 57VDC
- PoE Injector with AC Input 100VAC – 240VAC

Contact Us

- Email: sales@altaitechnologies.com

BX500X-PB-20220606

* May be limited by regulation

** Will be enabled via software upgrade

*** Depends on base station MTU size in case of PtMP operation

Although Altai has attempted to provide accurate information in these materials, Altai assumes no legal liability for the accuracy and completeness of the information. All specifications are subject to change without notice.